



# ift-Product Passport

Thermally toughened soda lime silicate safety glass (TSG-H) as per  
EN 12150-2 : 2005-01














No. 693 ESG 6040271-1-6  
14-003316-PR07 (PP-H01-11-en-03)



Valid until August 2021

Client	PRESS GLASS SA Nowa Wies Kopalniana 9 42-262 Poczesna Poland	
Production plants	PRESS GLASS SA ul. Cielmicka 44 PL 43-100 Tychy PRESS GLASS SA ul. Skarszewska 11 PL 83-110 Tczew	PRESS GLASS SA ul. Geodetów 4 PL 97-500 Radomsko PRESS GLASS d.o.o. Ul. dr. Marijana Mlinarica 5 HR 42203 Jalžabet
Product family 1	thermally toughened uncoated float glass	
Product family 2	thermally toughened enamelled float glass	
Product family 3	thermally toughened coated float glass	
Product designation	Toughened safety glass TG	
Mechanical strength	EN 12150-1	
Fragmentation	EN 12150-1	

## Performance characteristics (as per EN 14179-2 Annex ZA.1)

Characteristics	Resistance to fire	Reaction to fire	External fire behaviour	Bullet resistance	Explosion resistance	Burglar resistance	Pendulum body impact resistance
Class / Value	 npd	 A1	 npd	 npd	 npd	 npd	 1(C)1 1(C)2 <sup>*)</sup>
Characteristics	Thermal shock resistance	Resistance to wind, snow and permanent and imposed loads	Sound reduction index	Thermal properties	Light transmittance and reflectance	Solar energy characteristics	
Class / Value	 ΔT=200K	 3-19 mm	 R <sub>w</sub> <sup>*</sup>	 U <sub>g</sub> <sup>*</sup>	 npd	 npd	

npd = no performance determined  
<sup>\*)</sup> Value depends on product configuration

ift Rosenheim  
28.10.2018

*Christian Kehrer*

Christian Kehrer, Dipl.-Ing. (FH)  
Head  
Certification & Surveillance Body

*Alexander Meister*

Alexander Meister, Dipl.-Ing. (FH)  
Project Engineer  
Certification & Surveillance Body

### Basis

EN 14179-2 : 2005-08 Glass in building – Heat soaked thermally toughened soda lime silicate safety glass – Part 2: Evaluation of Conformity  
ift Certification Scheme - thermally toughened soda lime silicate safety glass (QM334)  
Product passport 603 8002966-1-2 dated 06.08.2012  
Product passport 14-003316-PR07 (PP-H04-11-de-03) dated 25.09.2018

### Instructions for use

The ift product passport demonstrates the general performance of the designated product families – determined on the basis of testing, calculation or assessment.

The values / classes indicated refer to the specific objects described in the individual evidence/certificates

Implementation of the performance characteristics is subject to the relevant national technical rules and regulations.

This product passport forms the basis for issuing the ift Certificate of Conformity which documents conformity of the end products and of factory production control by regular third party control of the manufacturer by the ift Rosenheim.

The product passport is valid for 3 years provided that the above-mentioned basis or the products do not change significantly during this time.

### Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies. The cover sheet can be used as abstract.

### Contents

The product passport contains a total of 16 pages:	
1 Overview, product family thermally toughened TSG	2
2 Classification matrix as per EN 12150-2	3
3 Product families and components	4
4 Performance characteristics as per product standard EN 12150-2	11
Special instructions for use	16