

Notified Body No. 2812

## Certificate of Constancy of Performance 2812-CPR-CA5003

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

### Cut Size AGC Pyrobel and Pyrobelite glasses, produced and placed on the market by Press Glass

Intended use: Laminated Glass and Laminated safety glass to be used in buildings and construction works.

Placed on the Market under the Name of

**Press Glass Sp. z o.o.**  
**ul. Golfowa 19**  
**42-274 Konopiska**  
**Poland**

and produced in the manufacturing plant

**Press Glass Sp. z o.o.**  
**The Division in Tczew**  
**Ul. Skarszewska 11**  
**83-110 Tczew**  
**Poland**

This certificate attests that all provisions concerning the Assessment and Verification of Constancy of Performance described in Annex ZA of the standard(s):

**EN 14449: 2005**

Under System (1) for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **22/12/2020** and revised on **21/04/2023** and will remain valid as long as neither the harmonised standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

CE Marking certificate valid to: **18/12/2023**

ERO Project Reference: **ERO 034621 P1973**



Paul Duggan  
Certification Manager

Notified Body No. 2812

## Certificate of Constancy of Performance 2812-CPR-CA5003

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

### Cut Size AGC Pyrobel and Pyrobelite glasses, produced and placed on the market by Press Glass

**Intended use: Laminated Glass and Laminated safety glass to be used in buildings and construction works.**

*Product parameter (levels and classes of performance of the product) "CE marking methods(s)" used if applicable; description of the product (identification and intended use(s), as the manufacturer intends for their declaration of performance):*

Product	AVCP System	Fire Resistance Classification
<b>Vertical Installations</b>		
Pyrobelite 7	1	EW30
Pyrobelite 13	1	EW30
Pyrobelite 12	1	EI20/EW60
Pyrobel 8	1	EI15/EW30
Pyrobel 16	1	EI30/EW60
	1	EI30
Pyrobel 17	1	EI45
Pyrobel 17N	1	EW60
	1	EI45/EW60
Pyrobel 21	1	EI45/EW60
Pyrobel 23	1	EI60
Pyrobel 23 EG	1	EI60
Pyrobel 25	1	EI60
Pyrobel 35	1	EI90
Pyrobel 53	1	EI120
Pyrobelite 7 EG/ Pyrobelite 11	1	EW30
Pyrobelite 12 EG	1	EI20/EW60
Pyrobel 8 EG	1	EI15/EW30
Pyrobel 16 EG	1	EI30/EW60
Pyrobel 17 EG	1	EI45
Pyrobel 17 N EG	1	EW60
	1	EI45/EW60
Pyrobel 21 EG	1	EI45/EW60
Pyrobel 25 EG	1	EI60
Pyrobel 30	1	EI90
Pyrobel 30 EG	1	EI90
Pyrobel 30 DGU	1	EI90
Pyrobel 35 EG	1	EI90
Pyrobel 53 EG	1	EI120
Pyrobel 53 N	1	EI120
Pyrobel 53 N EG	1	EI120
<b>Horizontal installations</b>		
Pyrobel 19H	1	EI30
Pyrobel 23H	1	EI45
Pyrobel 28H	1	EI60

\*Classification Reports (available on request from the glass manufacturer) define Fire Resistance Classification and is dependent on framing system and glazing configuration. The Classification Reports which determine the above EN13501-2 classifications detail the precise field of application for fire resistant applications within the scope of CE marking including product variants. Additional 'market application' tests or extended application reports may also be appropriate for use with CE marked glasses.

This Certificate of Constancy of Performance indicates groups of glass structures/designs. It is not possible to list all available glass structures/designs in detail. These are available in high diversity and described for each product in the Declaration of Performance.

The Declaration of Performance for each product configuration including the characteristics of performance is made available by the manufacturer.

CSF408-NL 7.0